



Height

-----

Shaft Diameter

\_\_\_\_\_

## Quality Hardwoods

Select & Better Grade, Sanded to 120  
Kiln Dried to 7-8%, 12 staves  
No Centers used, Riff Sawn  
Hardwood 1-1/2"(3.81cm) thick walls

## Interior Paint Grade

AmPoplar, Maple

## Interior Stain Grade

Alder, Sap White Maple, Red Oak  
Beech, Cherry, Walnut  
Basswood, African Mahogany  
White Ash, Yellow Birch

## Exterior Hardwood

White Pine, Knotty Pine  
Clear Pine (has few knots)  
Western Red Cedar  
White Oak

Select  
Left or Right



## SHAPE IT YOUR WAY:

Custom Heights available or  
Upgrade to Decorative Capitals or Attic Bases

## SPLIT COLUMNS FOR PILASTER!

Split in in half for Pilasters against a wall  
Note: Spiral thickness varies per diameter, drawing not to scale  
Rotation Length every 350mm (13-3/4")

\* All are designed as decorative items only. For load bearing applications request load bearing wood or use a metal post and wrap with Split column facade - you will loose the thickness of the saw blade when columns are split

\* All specifications subject to change without notice, Measurements are approximate & Final Product may vary from this brochure

